

SURFACE-EDGE
CONTRACT FLOORING

WWW.SURFACE-EDGE.COM



N E X T W O O D X L
WATERPROOF HARDWOOD

SURFACE-EDGE

CONTRACT FLOORING

WHO WE ARE

- An experienced contract furnishings group focused on innovative solutions for multi-family, builder, senior living, retail, corporate and hospitality projects.
- Amongst North America's largest flooring buyers with extensive global supply chain expertise.
- Exclusive North American representation for over a dozen high integrity, offshore flooring factories.
- Diverse product line focused on emerging trends and supported by advantages in price, style, quality and supply chain efficiency.

Multi Family



Senior Living



Corporate



Hospitality



Retail



N E X T W O O D X L

WATERPROOF HARDWOOD



Acadia



Dunes



Glacier



Muir



Zion

SPECIFICATIONS

Collection	Next Wood XL	Emissions	FloorScore
Size	6.5" x 72" (Random Length)	Installation Type	Locking (Floating)
Construction	Waterproof Wood (SPC core)	Locking System	Valinge
Thickness	6.5mm	Attached Pad	Yes
Surface Treatment	Thermal Treated	Warranty	Lifetime Limited Residential 10 Year Limited LT Commercial
Wear Layer	1.2mm Sliced	Sqft per Ctn	20
Embossing	Real Wood	Sqft per Pallet	66 Ctns = 1,320
Edge Detail	4 sided bevel	Sqft per Container	15 Pallets = 19,800
Finish	PowerShield™ with Aluminum Oxide		



GreenGuard Gold conforms with the strictest VOC and indoor air quality requirements.



NO ACCLIMATION

Can be installed as soon as the flooring arrives on site which significantly reduces costs and allows for faster turnarounds.



WATERPROOF

Real wood flooring that warrants up to 96 hours of water protection from spills.



DENT RESISTANT

The high density SPC core increases the dent resistance of the real wood veneer to over 2 X harder than solid oak flooring.



SOUND REDUCTION

Attached IXPE pad reduces sound transmission within a room as well as to the room below.



INCREASED STABILITY

Waterproof Wood structure reduces the effects of changes in temperature and humidity. Results in less cupping, gapping, and surface cracking.

PERFORMANCE TESTING

ASTM E90-2009 STC 61

ASTM E492-09 IIC 52

ISO 4918:2009 Caster Chair (25000 Rev.) Pass

ASTM D4060 Taber Abrasion Initial 1500 Rev.
Final 2500 Rev.

ASTM D2394 Coefficient Of Friction (COF) Dry 0.62
Wet 0.60

ASTM D5582 Formaldehyde <0.025ppm

Phthalates ND (Not Detected)

ASTM E648 Critical Radiant Flux Class 1

ASTM E662 Smoke Density-Flaming Passed
Smoke Density-Non-Flaming Passed

NALFA 3.5 Large ball impact Class 4

WATERPROOF HARDWOOD L A Y E R S



1 PROTECTIVE COATING

Durable and scratch resistant PowerShield Finish seals and protects wood surfaces from spills and stains

2 REAL WOOD VENEER

Hardwood veneer eliminates pattern repeats found in vinyl and laminate flooring

3 SPC CORE

Strong, Rigid, and 100% Waterproof SPC core installs without acclimation

4 LOCKING SYSTEM

Planks lock together and require no glue or nails for installation

5 SOUND LAYER

Attached foam under cushion decreases sound reflection and transmission